

Nuvo® P4300 Professional Series Player

Providing 110 watts of power per zone, this single rack-mount Professional Series Player (NV-P4300-UK) delivers high fidelity audio to three independent zones. Your music is always in hand with built-in access to streaming services and the ability to play content from networked computers and your iOS and Android devices. With a backlit touchscreen for configuration, system status, and the ability to show zone names, the P4300 Player is the latest generation of the Nuvo Professional Series Players.



- Built-in access to streaming services - Spotify, iHeartRadio, TuneIn, Napster, Deezer and SiriusXM
- Easily play music from networked computers, as well as iOS and Android devices.
- Backlit touchscreen supports easy setup with visible system status, zone names, and more
- A single rack-mount unit delivers high fidelity audio to three independent zones
- Efficient Class D amplifiers with 110 watts per zone at 8, 6 or 4 ohms
- Side mounted heat sinks and no fans for convenient single-space rack mounting
- 3.5mm combination analog/TOSLINK jacks for line inputs and outputs

*Streaming services subject to geographic availability. Service subscriptions may be required.

Nuvo® P4300

Professional Series

Player

Input/Output Connectors

Line Input	3.5mm combination analog / TOSLINK
Line Output	3.5mm combination analog / TOSLINK
Trigger Output	12 volt 3.5 mm
Speaker Output	14 ga. four position phoenix connectors
USB Connection	Three, One per zone
Local Area Network (LAN)	RJ45, Cat5 minimum, 10/100baseT minimum

Supported Audio Formats

Music File (USB or over network)	MP3
	WMA
	AAC
	Ogg Vorbis
	FLAC
	WAV

Internet Radio:	Pandora
	Sirius/XM
	iHeart Radio
	Napster
	Deezer
	Tuneln
	Spotify

IP Control	Apple iTouch®
	Apple iPhone®
	Apple iPad®
	Android Mobile
	Android Tablet

Network Connectivity

LAN (Wired Connection)	10/100base-t Ethernet
	Internal Ethernet switch to 3 independent zone nodes

Amplifier Output (typical of 3 zones)

Rated Output Power (1KHz / 1% Distortion)	4 / 6 / 8 Ohms - 110W per zone
---	--------------------------------

Distortion	.01 THD+N
Speaker Impedance	4 / 6 / 8 Ohms
Frequency Response (20 - 20kHz)	+/-1 dB
Signal-to-Noise Ratio (IHF-A)	104 dB on speaker output @ 4 Ohms

SPECIFICATIONS

Line Output:

Output Level	2 V RMS
Output Impedance	470 Ohms

Line Input:

Input Impedance	20K Ohms
Input Overload	2 V RMS

Regulatory Approvals

Safety	cTUVus, CE-LVD
EMC	US:FCC CFR Title 47 Part 15, Subpart B; CANADA:ICES-003; EUROPE:CISPR13; EUROPE: 55020; AUSTRALIA/NEW ZEALAND: C-TICK standard AS/NZS CISPR13
Environmental Compliance	RoHS

Power Requirements

Input Voltage	110 – 240VAC, 50/60 Hz
Power Consumption (max)	260 W
(typical - music)	50 W

Operating Temperature

0° C to 40° C

Physical Specifications

Unit Size without feet (mm)	47 H x 430 W x 258 D
Unit Size without feet (inch)	1.85 H x 16.93 W x 10.16 D
Unit Size with feet (mm)	54 H x 430 W x 258 D
Unit Size with feet (inch)	2.13 H x 16.93 W x 10.16 D
Unit Weight (kg)	2.9
Unit Weight (pounds)	6.45

Shipping Specifications

Unit Size (mm)	565 L x 330 W x 130 H
Unit Size (inch)	22.24 L x 12.99 W x 5.12 H
Unit Weight (kg)	3.92
Unit Weight (pounds)	8.65

Languages Supported

English, Spanish, French
Portuguese, German, Italian

Legrand reserves the right to change specifications without notice.



Legrand, UK & Ireland

Great King Street North
Birmingham
B19 2LF
T: +44 (0) 370 608 9000
www.legrand.co.uk